

BEST AVAILABLE COPY

Application Number: 10/738,348
 Art Unit: 2875

Page 2 of 5

AMENDMENTS TO THE CLAIMS:

Please amend the claims with the ones provided in the listing below wherein status, amendments, additions and cancellations are indicated.

1. (Currently amended) A motor vehicle reverse assistance light comprising:
 - 5 a housing which is an inverted U-shaped shell that includes: ~~utilized to hold a socket;~~
 - a receptacle and a locating tab formed inside said housing;
 - a threaded sleeve at one end of said inverted U-shaped shell of said housing;
 - 10 a stepped seating rim in said threaded sleeve;
 - a base which is a rectangular-shaped member that includes:
 - a rod and an arcuate groove formed on the said rectangular-shaped member of the said base;
 - the said rod on ~~the~~ said base member which is engaged within ~~the~~ - 15 said receptacle in ~~the~~ said housing shell so that said base it is rotatably conjoined to said housing it: ~~a~~ said locating tab in the said housing shell situated in ~~the~~ said arcuate groove on the said base member;
 - a socket having wire leads disposed on one end;
 - 20 a lamp hood that is a screw-on tube with a transparent outer cover fastened onto ~~a~~ said threaded sleeve; and ~~which further consists of:~~
 - a receptacle and a locating tab formed inside the said shell;
 - a threaded sleeve at one end of the said shell; and

BEST AVAILABLE COPY

Application Number: 10/738,348
Art Unit: 2875

Page 3 of 5

an LED a light emitting diode bulb cluster set onto the said socket,
which is then inserted inside said stepped seating rim in the said threaded
sleeve of the said housing.

2. (Currently amended) ~~As mentioned in Claim 1 of the~~ The motor vehicle
5 reverse assistance light in Claim 1, wherein of the invention herein, the said
receptacle in the said housing shell includes:

a semicircular retaining edge and a pair or more slots along ~~its~~ the
opening of said receptacle:

~~the~~ said rod on the said base member consisting of:

10 a rounded annular tip at the distal end;

a passage through the center;

~~the~~ said rounded annular tip on ~~the~~ said rod of ~~the~~ said base member
which is rotatably coupled by means of ~~the~~ said semicircular retaining edge
along the opening of the said receptacle in the said housing shell; and

15 ~~the~~ said wire leads ~~leading~~ on the said socket which are routed through
~~the~~ said passage centered in ~~the~~ said rod of the said base member.

3. (Currently amended) ~~As mentioned in Claim 1 of the~~ The motor vehicle
reverse assistance light in Claim 1, wherein of the invention herein, a
channel is formed along the lower side of said base member that proceeds
20 along one side of the said member up to the said passage in the center of the
said rod on ~~the~~ said member to facilitate the routing of ~~the~~ said wire leads
from the rear side of ~~the~~ said socket to the reverse light switch and electrical
ground connections.